

TECHNICAL DATA

DRILL-TERGE™

DÉTERGENT DE FORAGE / AGENT MOUILLANT

DESCRIPTION

DRILL-TERGE est une solution liquide de surfactant non-ionique formulée pour augmenter les propriétés détergentes et mouillantes des fluides de forage.

USAGE RECOMMANDÉ

Conçu pour contrôler la tension interfaciale et inhiber l'hydratation et la dispersion d'argile et de schiste.

CARACTÉRISTIQUES

- ▶ Assiste en gardant la mèche de forage propre et prévient le bourrage du trépan
- ▶ Conçu pour fonctionner dans l'eau douce ou salée
- ▶ Se mélange facilement
- ▶ Favorise le dépôt d'argile à la fosse/réservoir
- ▶ Réduit la torsion et le plissement associé au forage dans l'argile gonflante

MÉLANGE ET APPLICATIONS

Ajouter 2-3 quarts (6-9 litres) de DRILL-TERGE 100 gallons (par 1.1 m³) du liquide de forage bentonite existant.

EMBALLAGE

Seau de 45 lb (20.25 kg), 30 par palette ou baril de 495 lb (224.5 kg), 4 par palette. Toutes les palettes sont emballées avec du plastique.



2870 Forbs Avenue, Hoffman Estates, IL 60192
847.851.1800 | 800.527.9948 | cetco.com/dpg

IMPORTANT: The information contained herein supersedes all previous versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit cetco.com/dpg. CETCO accepts no responsibility for the results obtained through the application of this information. All weights are approximate. CETCO reserves the right to update information without notice. REV 1/11