



August 15, 2018

GF-60 FLASHING

LEED™ PRODUCT INFORMATION

GF-60 is a 60-mil reinforced thermoplastic UV resistant flashing membrane used with COREFLEX and other CETCO waterproofing systems.

MANUFACTURING LOCATION

CETCO certifies that GF-60 is manufactured in Cartersville, GA. If your project falls within a 500-mile radius of this location, the product is considered to be a locally produced material and can help contribute to earning Materials & Resources - Credit 5.1 and Credit 5.2.

RECYCLED CONTENT

CETCO certifies that GF-60 is manufactured with no pre-consumer or post-consumer material recycled content by weight.

VOC CONTENT

CETCO certifies that GF-60 contains 0 g/L Volatile Organic Compounds (VOCs). EQ Credit 4.1 and EQ Credit 4.2 pertains to materials that are to be used in the interior of the building.

CETCO waterproofing products are applied onto the exterior of the structure and therefore are not subject to the intent of EQ Credit 4.1 and EQ Credit 4.2. However, CETCO has provided the volatile organic content (VOC) of GF-60 herein.

CONSTRUCTION WASTE MANAGEMENT

In areas where facilities exist, the following GF-60 materials are recyclable and can contribute to earning MR Credit 2.1 and MR Credit 2.2:

Wood Pallet	wood	65-lbs
Roll Core	cardboard	3-lbs/core
Roll Spacer	cardboard	3-lbs/spacer

CETCO is committed to the use of recycled content in the manufacturing of CETCO waterproofing products and supports the United States Green Building Council (USGBC) by participating as an USGBC Industry Member.



Prepared by
Stacy Byrd, LEED AP
CETCO - Building Materials
National Products Manager

LEED is a trademark of the U.S. Green Building Council

