

SEAMTAPE

MULTI-PURPOSE JOINT TAPE

DESCRIPTION

SEAMTAPE is a single-sided tape consisting of an aggressive rubber-based adhesive with a durable polyethylene backing and release liner.

The inherent adhesive and waterproofing properties of the tape effectively splices the liner face of waterproofing membranes at the overlaps. SEAMTAPE provides good chemical resistance and excellent moisture resistance properties. Its flexibility allows the tape to be easily installed on irregular surface conditions. The adhesive is protected by a release liner that is removed during installation.

APPLICATIONS

SEAMTAPE is primarily used to seal the overlap seams of ULTRASEAL BT, SWELLTITE, VOLTEX DS/ DSCR for both backfilled foundation walls and horizontal deck applications. SEAMTAPE protects the overlap seams against debris intrusion during backfill and damage from rain prior to backfilling. SEAMTAPE may also be used in the repair of small tears or punctures in the outer geomembrane liner component of the waterproofing membrane. Additionally, SEAMTAPE is used to seal the overlap seams of GS-110 Root barrier in greenroof applications and used to seal open core edges of Aquadrain drainage composites.

PACKAGING

3" (75 mm) x 50-Ft (15.2 m) rolls
8 rolls per case

INSTALLATION

Clean the surface to receive SEAMTAPE. Surface should be free of dirt, dust, debris and moisture. Remove release liner. Install continuous line of SEAMTAPE centered on the membrane overlap with adhesive side against the membrane. Press firmly to adhere tape to membrane surface. Cut tape as required to install. Overlap all connecting tape ends a minimum 2" (50 mm) to form a continuous seal. Optimal results are obtained when tape is installed at temperatures 25°F (-4°C) or above.

SAFETY

Workers should wear protective clothing and eye protection. Do not ingest. Refer to MSDS for other warnings and product safety information.

North America: 847.851.1800 | 800.527.9948 | www.CETCO.com

UPDATED: JUNE 2015

© 2015 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.CETCO.com. CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.

FORM: TDS_SEAMTAPE_AM_EN_201506_V2

