

SODA ASH

SODIUM CARBONATE

DESCRIPTION

SODA ASH is the common name for sodium carbonate, which separates calcium into sodium and carbonate ions in solution.

RECOMMENDED USE

SODA ASH is used to raise the pH of make-up water for bentonite and polymer drilling fluids by precipitating soluble calcium. Using SODA ASH will increase the performance of bentonite and polymer drilling fluids.

ADVANTAGES

- Easy to mix and use
- Economical method to increase pH
- Maximizes yield of drilling fluid

MIXING AND APPLICATION

SODA ASH should be added slowly through a hopper or chemical barrel. When using a barrel, mix SODA ASH into a full barrel of freshwater and provide adequate agitation. Add SODA ASH until pH of 8.5-9.5 is obtained. Suggested ratio is 0.33 to 0.5 lb per 100 gallons (0.25 kg to 0.5 kg per 380 liters) water.

MIXING AND APPLICATION	
Physical Appearance	White Powder
pH (1 % solution)	11.4
Specific gravity	2.51
Solubility	51 g/100 ml at 86 °F (30 °C)

CHARACTERISTICS

PACKAGING

50 lb (22.7 kg) bags, 49 per pallet or 50 lb (22.7 kg) pails, 32 per pallet. All pallets are plastic-wrapped.

North America: 847.851.1800 | 800.527.9948 | www.CETCO.com

UPDATED: JULY 2015

© 2015 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.CETCO.com. CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.

